

DL10S
10W TRI-COLOUR DOWNLIGHT

KEY INFORMATION	
LUMEN OUTPUT	800-900 Lumens (3000k, 4000k, 5000k)
INPUT POWER	10W
REPLACES	50-75W Halogen
HOLE CUTOUT SIZE	90mm
INSTALL	Flat or recessed, spring clips
DIMMING OPTIONS	Dimmable
TRIM COLOUR	Matte white/Brushed chrome
WARRANTY	4 Years
IP RATING	IP44/IP40
FLICKER FREE	Yes

PHOTOMETRIC	
EFFICACY	Up to 90 Lms/W
LIGHT OUTPUT	Warm 3000k/Natural 4000k/Bright 5000k
CRI	>80
BEAM ANGLE	100°

ELECTRICAL	
DRIVER	Internal
SUPPLY INPUT	AC220-240V, 50-60Hz
POWER FACTOR	0.96
LIFESPAN	35000hrs

CONSTRUCTION	
MATERIAL CONSTRUCTION	Diecast aluminium with nano plastic, aluminium reflector
SHADE/HOUSING	Matte white flat/recessed, Brushed chrome flat, Matte white square, Matte white flat large 124mm
LOW HEAT OUTPUT	Low heat output
MERCURY	No Mercury
TOTAL WEIGHT	0.35kg
DIMENSIONS	Ø108mmx67mm
PACKED DIMENSIONS	113x113x82mm
CERTIFICATION	SAA, CE, RoHS, IC-4, RCM

DESCRIPTION:
LED colour changing light technology, fully dimmable, high CRI, high lumen output with good heat dissipation, no flickering and no UV. Unique with three popular and practical colour output options which are adjustable by switch on the back of the light to Warm (3000k), Natural (4000k) or Bright (5000k). Very economical and practical downlight option.

FEATURES:
Three colour output options adjustable by switch on the back of the light
Blue Filtered 5000k White, no green or unattractive colour hues
All 3 colours are attractive and usable
Built in Driver with cord and plug
Diffuser to give even spread of light and no visible LED
IC-4 Abutted and Covered certification allows covering with thermal insulation
Interchangeable cover options - Flat Matte White Recessed Matt White, Flat Brushed Chrome, Matte White Square and Matte White Large (124mm)





SUITABLE FOR:
General lighting applications:
Homes
Offices
Hotels
Shops
Schools