

P6S
6W LED MINI PANEL LIGHT

KEY INFORMATION	
LUMEN OUTPUT	3000k - 450Lm, 4000k - 450Lm, 5000k - 438Lm
INPUT POWER	6W
REPLACES	50W Traditional downlight
HOLE CUTOUT SIZE	55-10mm
INSTALL	Adjustable spring clips for recessed / Surface mounted with screws
DIMMING OPTIONS	Non-dimmable
TRIM COLOUR	White, Brushed chrome or Polished black chrome
WARRANTY	3 Years
IP RATING	IP20
FLICKER FREE	Yes

PHOTOMETRIC	
EFFICACY	75 Lm/W
LIGHT OUTPUT COLOUR	3000k/4000k/5000k - CCT switch adjustable
CRI	>80
BEAM ANGLE	110°

ELECTRICAL	
DRIVER	Internal
SUPPLY INPUT	240-265VAC, 50-60Hz
POWER FACTOR	>0.9
LIFESPAN	30000hrs

CONSTRUCTION	
MATERIAL CONSTRUCTION	Thermal plastic frame, PMMA, LGP, Aluminium
SHADE/HOUSING	White. Brushed chrome or polished black
LOW HEAT OUTPUT	Low heat output
MERCURY	No Mercury
TOTAL WEIGHT	0.3kg Packed
DIMENSIONS	Ø140x15mm
PACKED DIMENSIONS	160x145x6mm
CERTIFICATION	CE RCM SAA Plug

DESCRIPTION:
6W CEILING LIGHT -
Can fit various different hole sizes as well as solid ceilings. Unique, very versatile ceiling light with three popular and practical colour output options which are selected by switch on the back of the light; Warm (3000k), Natural (4000k) or Bright (5000k). Smooth dimming effect and no flickering. High CRI, high lumen output with good heat dissipation and no UV.

FEATURES:
Ultra slim, low profile
Surface mounted or recessed.
Adjustable fitting - hole size from 55-100mm.
Built in driver, cord and plug.
Flicker-free.
Comes standard with white cover.
Optional covers in polished chrome or black polished chrome.

SUITABLE FOR:
Domestic or commercial applications

