



## F100 100W CCT LED FLOOD LIGHT

### KEY INFORMATION

LUMEN OUTPUT	13000 Lumens
INPUT POWER	100W
HOLE CUTOUT SIZE	N/A
INSTALL	Easy to install angle bracket
DIMMING OPTIONS	Non-dimmable
TRIM COLOUR	Black
WARRANTY	3 Years
IP RATING	IP66 Weather proof
FLICKER FREE	Yes

### PHOTOMETRIC

EFFICACY	130Lms/Watt
LIGHT OUTPUT COLOUR	Warm White 3000k, Natural White 4000k, Bright White 5000k
CRI	>80
BEAM ANGLE	90° or 50x120°

### ELECTRICAL

DRIVER	Internal
SUPPLY INPUT	220-240VAC
POWER FACTOR	>0.9
LIFESPAN	>50000hrs

### CONSTRUCTION

MATERIAL CONSTRUCTION	Aluminium, Glass/PC
SHADE/HOUSING	Black with clear glass
LOW HEAT OUTPUT	Low heat output
MERCURY	No Mercury
NET WEIGHT	1.8Kg
DIMENSIONS	330x268x47.5mm
CERTIFICATION	SAA, RCM

### DESCRIPTION:

Strong, slim flood lights with high efficiency and long lifespan. Instant startup with low surface temperature.

Now with 3 colour-selectable colour temperature - 3000k (Warm), 4000k (Natural), 5000k (Bright White).

Available in 90° lens or asymmetric 50x120° - asymmetric lens gives ideal wall or pole mounted lighting in the direction and area required - covering a larger area with lower pole height.

### FEATURES:

Epistar SMD chip  
Very long lifespan >50 000 hrs  
Very efficient 130lm/Watt  
High power factor of  $\geq 0.9$   
Operating temperatures -40-+45°C  
SAA Plug and 1 m cord  
3 Year Warranty

### SUITABLE FOR:

Commercial/Public/Industrial lighting  
Homes  
Sheds  
Swimming Pool areas  
Passageways  
Workshops  
Public Areas  
Passageways  
Security