





412mm

KEY INFORMATION

LUMEN OUTPUT	26000 Lumens
INPUT POWER	200W
REPLACES	Up to 400W Halogen
HOLE CUTOUT SIZE	N/A
INSTALL	Easy to install angle bracket
DIMMING OPTIONS	Non-dimmable
TRIM COLOUR	Black
WARRANTY	3 Years
IP RATING	IP66 Weather proof
FLICKER FREE	Yes

PHOTOMETRIC EFFICACY 130Lms/Watt LIGHT OUTPUT COLOUR Bright White 5000k CRI >80 BEAM ANGLE 90° or 90x120°

ELECTRICAL

DRIVER	Internal
SUPPLY INPUT	220-240VAC
POWER FACTOR	>0.9
LIFESPAN	>50000hrs

CONSTRUCTION

MATERIAL CONSTRUCTION	Aluminium, Glass/PC
SHADE/HOUSING	Black with clear glass
LOW HEAT OUTPUT	Low heat output
NET WEIGHT	4.5Kg
DIMENSIONS	412x360x54mm
CERTIFICATION	SAA, RCM

F200 200W LED FLOOD LIGHT

DESCRIPTION:

Strong, slim flood lights with high efficiency and long lifespan. Instant startup with low surface temperature.

High quality LED chips with a long lifespan and very high quality Sosen driver giving high efficiency PF 0.9.

Available in 90° lens or 120° lens.

New 50x120° <u>asymmetric</u> lens coming soon - asymmetric lens gives ideal wall or pole mounted lighting in the direction and area required - covering a larger area with lower pole height.

FEATURES:

Epistar SMD chip Sosen driver Very long lifespan 50 000 hrs Very efficient 130lm/Watt High power factor of ≥0.9 Operating temperatures -40~+45°C SAA Plug and 1m cord 3 Year Warranty

SUITABLE FOR:

Commercial/Public/Industrial lighting Homes Sheds Swimming Pool areas Passageways Workshops Public Areas Passageways Security