



F50W 50W LED SUPER SLIM FLOODLIGHT

KEY INFORMATION

LUMEN OUTPUT	5000Lumens
INPUT POWER	50W
REPLACES	Up to 500W Halogen Flood
HOLE CUTOUT SIZE	N/A
INSTALL	Mounting bracket, surface mounted
DIMMING OPTIONS	Non-dimmable
TRIM COLOUR	White
WARRANTY	2 Years
IP RATING	IP65 Weather proof
FLICKER FREE	Yes

PHOTOMETRIC

EFFICACY	100Lms/Watt
LIGHT OUTPUT COLOUR	Natural White 4000k
CRI	>80
BEAM ANGLE	120°

ELECTRICAL

DRIVER	Internal
SUPPLY INPUT	180-260VAC, 50-60Hz
POWER FACTOR	0.9
LIFESPAN	25000hrs

CONSTRUCTION

MATERIAL CONSTRUCTION	Aluminium alloy housing & 316 marine-grade stainless steel
SHADE/HOUSING	White with clear glass
LOW HEAT OUTPUT	Low heat output
MERCURY	No Mercury
TOTAL WEIGHT	575g
DIMENSIONS	220x155x18mm
PACKED DIMENSIONS	230x188x38mm
CERTIFICATION	CE, RoHS, RCM

DESCRIPTION:

Super slim, elegant, compact and strong floodlights. Made from pressure-cast aluminium, the surface has been treated with electrostatic coating and is characterised by strong adhesion. With blue filtered 4000k white light which is both comfortable and attractive. Unique slim mounting bracket which allows for easy, versatile installation and very close fitting. Attractive white with grey reflector and housing to blend in and suit high quality finishes. Available in 10w, 20w, 30w, 50w, 100w.

FEATURES:

- Water resistant IP65
- Corrosion proof
- Die-cast aluminium
- 316 marine-grade stainless steel
- Blue filtered
- Operating temperature -25° ~+45°C
- Easy installation
- Slim design allows
- Optional waterproof connector and SAA plug
- 3 Year Warranty

SUITABLE FOR:

- Homes
- Sheds
- Gardens
- Other outdoor lighting applications

