



## F50 CCT 50W LED FLOOD LIGHT COLOUR SELECTABLE

### KEY INFORMATION

LUMEN OUTPUT	5000 Lumens
INPUT POWER	50W
HOLE CUTOUT SIZE	N/A
INSTALL	Easy to install angle bracket
DIMMING OPTIONS	Non-dimmable
TRIM COLOUR	Black
WARRANTY	3 Years
IP RATING	IP66 Weather proof
FLICKER FREE	Yes

### PHOTOMETRIC

EFFICACY	100Lms/Watt
LIGHT OUTPUT COLOUR	Warm White 3000k, Natural White 4000k, Bright White 5000k (selectable)
CRI	>80
BEAM ANGLE	90°/120°

### ELECTRICAL

DRIVER	Internal
SUPPLY INPUT	220-240VAC
POWER FACTOR	>0.9
LIFESPAN	>50000hrs

### CONSTRUCTION

MATERIAL CONSTRUCTION	Aluminium, Glass/PC
SHADE/HOUSING	Black with clear glass
LOW HEAT OUTPUT	Low heat output
MERCURY	No Mercury
NET WEIGHT	1Kg
DIMENSIONS	252x213x43.5mm
CERTIFICATION	SAA, RCM

#### DESCRIPTION:

Strong, slim flood lights with high efficiency and long lifespan. Instant startup with low surface temperature.

CCT with 3 colour selectable switch - 3000k or 4000k or 5000k

Available in 90° or 120° lens

#### FEATURES:

Epistar SMD chip  
Very long lifespan 50 000 hrs  
Very efficient 100lm/Watt  
High power factor of >0.9  
Operating temperatures -40~+45°C  
SAA Plug and 1 m cord  
3 Year Warranty

#### SUITABLE FOR:

Commercial/Public/Industrial lighting  
Homes  
Sheds  
Swimming Pool areas  
Passageways  
Workshops  
Public Areas  
Passageways  
Security