

GH-F50S-CCT

50W WHITE FLOOD CCT PA



KEY INFORMATION

LUMEN OUTPUT	3150-6250Lms
POWER	30/40/50W
INSTALL	Wall mount
WARRANTY	3 Years
LIFESPAN	30000Hrs
IP RATING	IP65
IK RATING	IK06
HOUSING COLOUR	White
OPERATING TEMP	-25°C - 50°C

PHOTOMETRIC

EFFICACY	Up to 125 lumens/watt
COLOUR SELECTABLE	3000/4000/5000k
BEAM ANGLE	100°
CRI	80

ELECTRICAL

INPUT VOLTAGE	AC220-240 50/60Hz
---------------	-------------------

CONSTRUCTION

MATERIAL CONSTRUCTION	Rugged diecast aluminium, PC, Glass
DIMENSIONS	76x128.5x120mm
WEIGHT	0.81kg
CERTIFICATION	RCM, Australian Certified

DESCRIPTION:

NEW Very versatile, slim, compact, strong floodlight. High lumen efficiency with a power factor ≥ 0.9 . It is water and dust resistant (IP65), made from diecast aluminium for excellent heat dissipation.

Colour temperature is adjustable by switch - warm white (3000k) or natural white (4000k) or bright white (5700k) as well as power adjustable by switch - 30w or 40w or 50w.

FEATURES:

- Easy to adjust
- Die-cast Aluminium housing for excellent heat dissipation
- Colour Selectable - 3000k/4000k/5700k
- Power Selectable - 30w/40w/50w

SUITABLE FOR:

- Outdoor lighting applications
- Wide lighting area
- Security



MODEL	WATTAGE	LUMENS	CCT
GH-F50S-CCT	50W	31450-6250Lms	3000/4000/5000k