



DL13ES 13W TRI-COLOUR DOWNLIGHT

KEY INFORMATION

LUMEN OUTPUT	1050/1320/1170 Lumens (3000k, 4000k, 5000k)
INPUT POWER	13W
REPLACES	120Watt
HOLE CUTOUT SIZE	110mm
INSTALL	Recessed, spring clips
DIMMING OPTIONS	Dimmable 10-100%
TRIM COLOUR	Matte white
WARRANTY	4 Years
IP RATING	IP54/IP40
FLICKER FREE	Yes

PHOTOMETRIC

EFFICACY	Up to 101 Lms/W
LIGHT OUTPUT COLOUR	Warm 3000k/Natural 4000k/Bright 5000k
CRI	80
BEAM ANGLE	100°

ELECTRICAL

DRIVER	Internal
SUPPLY INPUT	AC200-240V, 50-60Hz
POWER FACTOR	0.95
LIFESPAN	40000hrs

CONSTRUCTION

MATERIAL CONSTRUCTION	Aluminium,, PCB, PMMA
SHADE/HOUSING	Matte white Flat
LOW HEAT OUTPUT	Low heat output
MERCURY	No Mercury
TOTAL WEIGHT	0.33kg
DIMENSIONS	Ø145mmx62.5mm
PACKED DIMENSIONS	155x155x70mm
CERTIFICATION	SAA, CE, IC-4, RCM

DESCRIPTION:

LED switch changeable downlight to fit larger hole size 130-140mm

FEATURES:

Match 0W downlight, fits oversize hole 120-130mm
Dimmable 10-100%. (1-100% with certain dimmers)
Three usable colour options - Warm (3000k), Natural (4000k) or bright (5000k).
High CRI and High Lumen output.
Built in driver with IC-4 and SAA certification
Cord and plug
No flickering & no UV
IP54 base, suitable for patios and eaves

SUITABLE FOR:

Homes
Offices
Hotels
Schools
Shops