

5/7/10W 360° GIMBAL DIMMABLE LED DOWNLIGHT IP65

5W - 40mm
7W - 40mm
10W - 45mm



← →
Ø75mm - 5W
Ø95mm - 7W
Ø110mm - 10W

KEY INFORMATION

LUMEN OUTPUT	500/700/1000 Lumens
INPUT POWER	5/7/10W
HOLE CUTOUT SIZE	60/70/90mm
INSTALL	Flat surface, spring clips
DIMMING OPTIONS	Dimmable 0-100%
TRIM COLOUR	Matte White or Matte Black (7w/10w)
WARRANTY	3 Years
IP RATING	IP65 waterproof, dust proof, Driver IP20
FLICKER FREE	Yes

PHOTOMETRIC

EFFICACY	Up to 100 Lms/W
LUMEN OUTPUT COLOUR	Warm 3000k/Natural 4000k/Bright 6000k
CRI	≥80
BEAM ANGLE	60°

ELECTRICAL

DRIVER	External
SUPPLY INPUT	AC220-240V, 50-60Hz
POWER FACTOR	>0.92
LIFESPAN	50000Hrs

CONSTRUCTION

MATERIAL CONSTRUCTION	Aluminium and PMMA
SHADE/HOUSING	Matte White or Matte Black Recessed
LOW HEAT OUTPUT	Yes
TOTAL WEIGHT	250/400/500g/pce
DIMENSIONS	Ø75mmx40mm/Ø95mmx40mm/Ø110x45mm
CERTIFICATION	SAA, IC-4, RCM, IP65

DESCRIPTION:

NEW Fully sealed, compact gimbal downlight with high CRI, high lumen output, long lifespan and long warranty. Very good quality, good heat dissipation with no flickering and no UV. Fast, push-fit termination with separate driver, dimmable, beam angle of 60° for even spread of light and less glare. With short circuit and overload protection.

FEATURES:

- 60° Beam angle for spot lighting & less glare
- Class II with double insulation
- Dimmable from 0-100%
- All three colours are attractive and usable in a variety of environments
- Warm (3000k), Natural (4000k) or Bright (5700k)
- Maximum depth of 45mm for shallow and void ceiling
- High CRI and High Lumen output
- No flickering and no UV
- IP65 - Waterproof and dust-proof
- Short circuit and overload protection
- 3 Year Warranty

SUITABLE FOR:

- Homes, Offices, Shops, Hotels
- Domestic, Retail, Commercial