



## 200W SMART LED HIGH BAY 120° BEAM ANGLE

### KEY INFORMATION

LUMEN OUTPUT	32 000 Lumens
INPUT POWER	200W Power Adjustable
HOLE CUTOUT SIZE	N/A
INSTALL	Hanging bracket with ring
DIMMING OPTIONS	Dimmable with Sensor option
TRIM COLOUR	Black
WARRANTY	4 Years
IP RATING	IP66 - waterproof/dustproof
IK RATING	IK10
FLICKER FREE	Yes

### PHOTOMETRIC

EFFICACY	160Lm/W
LIGHT OUTPUT COLOUR	CCT Selectable 3000/4000/5000K
CRI	>80
BEAM ANGLE	120°

### ELECTRICAL

DRIVER	Internal flicker free
SUPPLY INPUT	100~277VAC, 50-60Hz
POWER FACTOR	>0.9
LIFESPAN	50 000hrs

### CONSTRUCTION

MATERIAL CONSTRUCTION	ADC112 Aluminium, electrostatic polyester powder coating, optical grade PC anti-UV lens
SHADE/HOUSING	Black Aluminium
LOW HEAT OUTPUT	Low heat output
TOTAL WEIGHT	2.7kg Packed
DIMENSIONS	Ø335x156mm
PACKED DIMENSIONS	36x36x14cm
CERTIFICATION	SAA, RCM

### DESCRIPTION:

NEW lightweight, high brightness (160 lumens/watt), CCT and power adjustable range LED High Bay light in 200w. High quality Philips LED chips with long lifespan and high efficiency. Huge energy savings with PF >0.9. Quick and easy installation to minimise retrofit costs.

Precise lens technology provides light exactly where it is needed, reducing light wastage. Excellent thermal design ensuring safe working temperature and long life.

This light is Smart-Ready, CCT and Power Adjustable, Sensor available as an option.

### FEATURES:

High reliability, high stability, high colour rendering  
Available in 120° beam suitable for ceiling heights of 4-6m  
Operating temperature -35~+45°C  
Waterproof (IP66)  
PF >0.90  
Extremely long lifespan 50000hrs  
4 Year Warranty

### SUITABLE FOR:

Sheds/Factories/Warehouses/Garages/  
Supermarkets/Gyms/Schools/High ceilings (6m or less)/General open areas



