GH-W50CCT LED WALL LIGHT



| KEY INFORMATION | | | | |
|------------------------|--|--|--|--|
| LUMEN OUTPUT | 2800-7000Lms | | | |
| INPUT POWER ADJUSTABLE | 20/30/40/50W | | | |
| INSTALL | Wall Mount | | | |
| WARRANTY | 5 Years | | | |
| LIFESPAN | 50000Hrs | | | |
| IP RATING | IP65 | | | |
| IK RATING | 8 | | | |
| HOUSING COLOUR | Dark bronze polyester powder-coat finish | | | |
| OPERATING TEMP | -40°C - 40°C | | | |
| PHOTOMETRIC | | | | |
| EFFICACY | 140Lm/W | | | |
| COLOUR SELECTABLE | 4000K/5000K/6500K | | | |
| BEAM ANGLE | 60x120° | | | |
| CRI | 80 | | | |
| ELECTRICAL | | | | |
| INPUT VOLTAGE | 120-277 VAC Input Voltage | | | |
| CONSTRUCTION | | | | |
| MATERIAL CONSTRUCTION | Rugged diecast aluminium , corrosion resistant housing | | | |
| DIMENSIONS | 281mmx216mmx100mm | | | |
| CERTIFICATION | RCM (Australian Certified), SAA Driver | | | |

DESCRIPTION:

GH-W50 CCT is IP65 rated, it is fully gasketed with a one-piece solid silicone gasket to keep out moisture and dust. Power Factor =>0.9

Its well-crafted reflector optics provide visual comfort, superior light distribution and uniformity in wall-mount applications. It has a 0 to +90° tilt adjustment. Multi-purpose and can be used in both commercial and domestic applications.

SUITABLE FOR:

- Commercial or domestic applications
- Hospitals, schools, malls etc.
- Restaurants, retail areas

Power Adjustable - 20/30/40/50W Colour Selectable - 4000k/5000k/6500k



















| MODEL | WATTAGE | LUMENS | EFFICACY | CCT |
|-----------|--------------|--------------|----------|-----------------|
| GH-W50CCT | 20/30/40/50W | 2800-7000Lms | 140 Lm/W | 4000/5000/6500k |