



P18E 18W LED MINI PANEL

KEY INFORMATION

LUMEN OUTPUT	4000k - 1400Lumens / 5000k - 1450Lumens
INPUT POWER	18W
REPLACES	2 Bulb Oyster fitting / 120W traditional downlight / 44CFL
HOLE CUTOUT SIZE	From 60-200mm
INSTALL	Spring clips or surface mount with screws. Surface mounted or recessed
DIMMING OPTIONS	Non-dimmable
TRIM COLOUR	White
WARRANTY	3 Years
IP RATING	IP40
FLICKER FREE	Yes

PHOTOMETRIC

EFFICACY	Up to 80Lm/W
LIGHT OUTPUT COLOUR	4000k/5000k
CRI	>80
BEAM ANGLE	120°

ELECTRICAL

DRIVER	Internal
SUPPLY INPUT	200-240VAC, 50-60Hz
POWER FACTOR	>0.5
LIFESPAN	30000hrs

CONSTRUCTION

MATERIAL CONSTRUCTION	White PC frame, aluminium heatsink
SHADE/HOUSING	White with frosted PC lens
LOW HEAT OUTPUT	Low heat output
MERCURY	No Mercury
TOTAL WEIGHT	0.34kg
DIMENSIONS	Ø230x15mm
PACKED DIMENSIONS	275x239x30mm
CERTIFICATION	CE RCM SAA IC-4

DESCRIPTION:

18W CEILING LIGHT -

Can replace multiple Downlight sizes as well as Oyster Light Replacement. Unique, very versatile ceiling light in two popular and practical colour output options - Natural (4000k) or Bright (5000k). No flickering with high CRI, high lumen output, good heat dissipation and no UV. Perfect for a small room or bathroom, large surface area reduces glare and gives good light spread.

FEATURES:

Surface mounted or recessed.
Strong, Compact, neat and very Bright
Adjustable fitting. Hole size from 60-200mm.
Built in driver, cord and plug.
Flicker-free.

SUITABLE FOR:

Domestic or commercial applications
Homes
Schools
Offices