



P36P 60X60 36W LED LOW GLARE PANEL (BACK-LIT)

KEY INFORMATION

LUMEN OUTPUT	3600 Lumens
INPUT POWER	36W
REPLACES	2 x 1.2m Tubes
HOLE CUTOUT SIZE	N/A
INSTALL	Fits suspended ceilings
DIMMING OPTIONS	Non-dimmable (dimmable drivers optional)
TRIM COLOUR	White
WARRANTY	3 Years
IP RATING	IP40
FLICKER FREE	Yes

PHOTOMETRIC

EFFICACY	100Lm/W
LIGHT OUTPUT COLOUR	5000k - Bright white. Blue filtered.
CRI	≥80
BEAM ANGLE	90°

ELECTRICAL

DRIVER	Internal
SUPPLY INPUT	200-240VAC, 50-60Hz
POWER FACTOR	≥0.9
LIFESPAN	50 000hrs

CONSTRUCTION

MATERIAL CONSTRUCTION	Aluminium frame, PMMA and PC diffuser
SHADE/HOUSING	Slim, flat white frame with frosted lens
LOW HEAT OUTPUT	Low heat output
MERCURY	No Mercury
TOTAL WEIGHT	1.9kg
DIMENSIONS	595x595x32mm
PACKED DIMENSIONS	660x675x32mm
CERTIFICATION	CE, RCM, SAA, IC-4

DESCRIPTION:

New technology premium back-lit panels are more efficient with lower operational costs. Perfect for commercial use. Excellent energy saving and very efficient. Low UGR, flicker-free driver, no RF interference, no UV radiation.

FEATURES:

Low UGR<19 can reduce over 50% glare into eyes, increasing comfort and productivity. High Brightness - 100 Lumen/Watt LED's, 36Watt panel provides more light than 2 x 1.2m T8 fluorescent tubes. 50 000 hrs lifespan
Square (60x60cm) or rectangular (30x120cm)
3 Year Warranty
100% flicker free drivers
PF=≥0.9
5000k Blue filtered
Fits easily to suspended ceilings

SUITABLE FOR:

Commercial use:
Schools and Educational Facilities
Offices
Hospitals
Healthcare
Retail
Showrooms