

GH-WL10PB

10w Up/Down Slim Wall Light



KEY INFORMATION	WL10PB
LUMEN OUTPUT	730-820Lm
POWER	10W - 5w Up/ 5w Down
INSTALLATION	Wall Mount
LED DRIVER	Built-in Driver
DIMMING	Non Dimmable
PHOTOMETRIC	
EFFICACY	Up to 82 Lms/Watt
COLOUR SELECTABLE	3 -CCT: 3000K/4000K/5700K
BEAM ANGLE	120°
CRI	80
INPUT VOLTAGE	AC220-240V, 50-60Hz
CONSTRUCTION	
MATERIAL CONSTRUCTION	Aluminium + PC
SHADE/HOUSING	Black
IP RATING / IK RATING	IP65/IK08
WARRANTY	2 Years
LIFESPAN	50000Hrs
OPERATING TEMP	-20°C~45°C
DIMENSIONS	175 x 90 x 30 mm
WEIGHT	0.57kg
CERTIFICATION	Global Mark, Australian Certified

DESCRIPTION:

The **10w Up/Down Wall Light** is a contemporary architectural light designed to create a refined ambient lighting effect.

Featuring a high-efficiency light source paired with a premium PC diffuser, it delivers a soft, even and glare-free illumination.

It produces a subtle halo effect, enhancing walls with warm, atmospheric light.

Constructed from durable diecast aluminium, the housing provides excellent thermal management for long-lasting performance and reliability and is IP65 Water resistant.

FEATURES:

- ADC12 diecast aluminium housing provides excellent thermal management and long-lasting durability.
- Ultra thin, only 30.5mm in width
- Can be used indoors or outdoors
- Selectable colour temperature (3000K / 4000K/ 5700K) via an integrated slide switch.
- IP65-rated for reliable performance in both indoor and outdoor applications.
- Integrated flicker-free LED driver ensures smooth, comfortable illumination.

SUITABLE FOR: Commercial, Domestic



MODEL	WATTAGE	LUMENS	EFFICACY	CCT
WL10PB	10W - 5w Up/ 5w Down	730-820Lm	Up to 82Lm/Watt	3-CCT 3000/4000/5700K