



KEY INFORMATION	
WIFI STANDARD	WiFi 802.11 b/g/n 2.4GHZ
DETECTION	Opening and closing of the window/door from a fixed position
DETECTION DISTANCE	10-20m
WIRELESS CONNECTION	Zigbee
OPERATING TEMPERATURE	-20°C - 60°C
INSTALLATION	Paste and fix
PLACEMENT	Avoid an environment with magnetic field interference

ELECTRICAL	
SUPPLY INPUT	2.3-3.3V 3V CR2032 Battery
WARRANTY	1 Year

CONSTRUCTION		
MATERIAL CONSTRUCTION	White ABS & PC	
SHADE/HOUSING	White with blue indicator light	
TOTAL WEIGHT	17g	
DIMENSIONS	42x25x12mm	
PACKED DIMENSIONS	84x84x18mm	
CERTIFICATION	RCM, CE	



## ZI SENSOR - DOOR ZIGBEE CONTACT SENSOR

## **DESCRIPTION:**

SMART ZigBee Magnetic Contact Sensor works with Zigbee Smart Gateway via WiFi. Small and versatile with no wiring required, can be located conveniently anywhere in a home, garage or office/business premises. With long battery life, easy installation and use. Consists of main unit and magnet. Can be used to detect the opening and closing status of windows, doors, sheds, cabinets etc. When the contact is broken, notification will be sent to your phone/SMART device and record to the Cloud. Indoor use only.

## **FEATURES:**

Magnetic sensor 2.4Ghz 3V Battery

Detection range: 10-20m

## SUITABLE FOR:

Garages Windows Warehouses