



F150 CCT 150W LED FLOOD LIGHT COLOUR SELECTABLE

DESCRIPTION:

Strong, slim flood lights with high efficiency and long lifespan. Instant startup with low surface temperature. Available in 50W/150W with 3 colour selectable switch - 3000k or 4000k or 5000k

FEATURES:

Epistar chips Very long lifespan 50 000 hrs Very efficient 120lm/Watt High power factor of ≥0.95 3 Year Warranty

SUITABLE FOR:

Homes
Sheds
Swimming Pool areas
Passageways
Workshops
Public Areas
Passageways
Security

| KEY INFORMATION | | |
|------------------|---------------------------------|--|
| LUMEN OUTPUT | 18000 Lumens | |
| INPUT POWER | 150W | |
| REPLACES | Brighter than 400W Metal Halide | |
| HOLE CUTOUT SIZE | N/A | |
| INSTALL | Mounting bracket | |
| DIMMING OPTIONS | Non-dimmable | |
| TRIM COLOUR | Black | |
| WARRANTY | 4 Years | |
| IP RATING | IP66 Weather proof | |
| FLICKER FREE | Yes | |

| PHOTOMETRIC | |
|------------------------|--|
| EFFICACY | 120Lms/Watt |
| LIGHT OUTPUT COLOUR | Warm White 3000k, Natural White 4000k, Bright White 5000k (selectable) |
| CRI | 80 |
| BEAM ANGLE | 90° |

| ELECTRICAL | |
|--------------|---------------------|
| DRIVER | Internal |
| SUPPLY INPUT | 200-240VAC, 50-60Hz |
| POWER FACTOR | ≥0.95 |
| LIFESPAN | 50000hrs |

| CONSTRUCTION | |
|-----------------------|--------------------------------------|
| MATERIAL CONSTRUCTION | Diecast aluminium and tempered glass |
| SHADE/HOUSING | Black with clear glass |
| LOW HEAT OUTPUT | Low heat output |
| MERCURY | No Mercury |
| NET WEIGHT | 4.8kg |
| DIMENSIONS | 395x325x56mm (without bracket) |
| PACKED DIMENSIONS | 430x450x125mm |
| CERTIFICATION | SAA, RCM |