54mm

412mm

360mm

greenhse
Technologies

F150 CCT
150W LED TRI-COLOUR
FLOOD LIGHT

DESCRIPTION:
Strong, slim flood lights with high efficiency and long lifespan. Instant startup with low surface temperature.

Available in 90° lens or asymmetric 90x120° - asymmetric lens gives ideal wall or pole mounted lighting in the direction and area required - covering a larger area with lower pole height.

FEATURES:
Epistar SMD chip
Three colour selectable output light
Very long lifespan 50 000 hrs
Very efficient 130lm/Watt
High power factor of >0.9
Operating temperatures -40~+45°C
SAA Plug and 1 m cord
3 Year Warranty

SUITABLE FOR:
Commercial/Public/Industrial lighting
Homes
Sheds
Swimming Pool areas
Passageways
Workshops
Public Areas
Passageways
Security

KEY INFORMATION

LUMEN OUTPUT	19500 Lumens
INPUT POWER	150W
REPLACES	Up to 400W Halogen
HOLE CUTOUT SIZE	N/A
INSTALL	Easy to install angle bracket
DIMMING OPTIONS	Non-dimmable
TRIM COLOUR	Black
WARRANTY	3 Years
IP RATING	IP66 Weather proof
FLICKER FREE	Yes

PHOTOMETRIC

EFFICACY	130Lms/Watt
LIGHT OUTPUT COLOUR	Warm White 3000k or Natural White 4000k or Bright White 5000k
CRI	>80
BEAM ANGLE	120°

ELECTRICAL

DRIVER	Internal
SUPPLY INPUT	220–240VAC
POWER FACTOR	>0.9
LIFESPAN	>50000hrs

CONSTRUCTION

MATERIAL CONSTRUCTION	Aluminium, Glass/PC
SHADE/HOUSING	Black with clear glass
LOW HEAT OUTPUT	Low heat output
NET WEIGHT	4.5Kg
DIMENSIONS	412x360x54mm
CERTIFICATION	SAA, RCM