



F200 200W LED FLOOD LIGHT

DESCRIPTION:

Strong, slim flood lights with high efficiency and long lifespan. Instant startup with low surface temperature.

Available in 90° lens or asymmetric 90x120° - asymmetric lens gives ideal wall or pole mounted lighting in the direction and area required - covering a larger area with lower pole height.

FEATURES:

- Epistar SMD chip
- Very long lifespan 50 000 hrs
- Very efficient 130lm/Watt
- High power factor of ≥ 0.9
- Operating temperatures -40~+45°C
- SAA Plug and 1 m cord
- 3 Year Warranty

SUITABLE FOR:

- Commercial/Public/Industrial lighting
- Homes
- Sheds
- Swimming Pool areas
- Passageways
- Workshops
- Public Areas
- Passageways
- Security

KEY INFORMATION

LUMEN OUTPUT	26000 Lumens
INPUT POWER	200W
REPLACES	Up to 400W Halogen
HOLE CUTOUT SIZE	N/A
INSTALL	Easy to install angle bracket
DIMMING OPTIONS	Non-dimmable
TRIM COLOUR	Black
WARRANTY	3 Years
IP RATING	IP66 Weather proof
FLICKER FREE	Yes

PHOTOMETRIC

EFFICACY	130Lms/Watt
LIGHT OUTPUT COLOUR	Bright White 5000k
CRI	>80
BEAM ANGLE	90° or 90x120°

ELECTRICAL

DRIVER	Internal
SUPPLY INPUT	100-277VAC
POWER FACTOR	>0.9
LIFESPAN	>50000hrs

CONSTRUCTION

MATERIAL CONSTRUCTION	Aluminium, Glass/PC
SHADE/HOUSING	Black with clear glass
LOW HEAT OUTPUT	Low heat output
MERCURY	No Mercury
NET WEIGHT	4.5Kg
DIMENSIONS	412x360x54mm
CERTIFICATION	SAA, RCM