



F60W 60W LED FLOOD LIGHT

KEY INFORMATION

LUMEN OUTPUT	7200 Lumens
INPUT POWER	60W
REPLACES	Up to 400W Metal Halide
HOLE CUTOUT SIZE	N/A
INSTALL	Mounting bracket
DIMMING OPTIONS	Non-dimmable
TRIM COLOUR	Black
WARRANTY	5 Years
IP RATING	IP65 Weather proof
FLICKER FREE	Yes

PHOTOMETRIC

EFFICACY	120Lms/Watt
LIGHT OUTPUT COLOUR	Bright White 5000k
CRI	>80
BEAM ANGLE	120°

ELECTRICAL

DRIVER	Internal
SUPPLY INPUT	190-260VAC, 50-60Hz
POWER FACTOR	0.99
LIFESPAN	60000hrs

CONSTRUCTION

MATERIAL CONSTRUCTION	Diecast aluminium and tempered glass
SHADE/HOUSING	Black with clear glass
LOW HEAT OUTPUT	Low heat output
MERCURY	No Mercury
TOTAL WEIGHT	1.5kg
DIMENSIONS	310x220x47.5mm (with bracket), 265x220x45.5mm (without bracket)
PACKED DIMENSIONS	355x255x55mm
CERTIFICATION	CE, RoHS

DESCRIPTION:

Strong, slim flood lights with high efficiency and long lifespan. Instant startup with low surface temperature. Available in 30W/60W/100W/150W/200W.

60° Options also available for 3 x stronger light over longer distances

FEATURES:

Philips chip
Very long lifespan 60 000 hrs
Very efficient 120 lm/Watt
High power factor of 0.99
5 Year Warranties

SUITABLE FOR:

Workshops
Warehouses
Buildings
Security
Large Sheds
Area Lighting