



DL10PS 10W 60° BEAM DOWNLIGHT

KEY INFORMATION

LUMEN OUTPUT	800-980 Lumens
INPUT POWER	10W
REPLACES	100-120Watt
HOLE CUTOUT SIZE	90-95mm
INSTALL	Flat, spring clips
DIMMING OPTIONS	Dimmable 8-100%
TRIM COLOUR	Matte white
WARRANTY	4 Years
IP RATING	IP54/IP40
FLICKER FREE	Yes

PHOTOMETRIC

EFFICACY	Up to 98 LMS/W
LIGHT OUTPUT	3000/4000/5000k
CRI	>80
BEAM ANGLE	60° Anti glare

ELECTRICAL

DRIVER	Internal
SUPPLY INPUT	AC220-240V, 50-60Hz
POWER FACTOR	
LIFESPAN	50000hrs

CONSTRUCTION

MATERIAL CONSTRUCTION	Plastic coated aluminium
SHADE/HOUSING	Matte white flat
LOW HEAT OUTPUT	Low heat output
MERCURY	No Mercury
TOTAL WEIGHT	0.2kg
DIMENSIONS	Ø115mmx61mm
PACKED DIMENSIONS	125x125x70mm
CERTIFICATION	SAA, IC-4, RCM

DESCRIPTION:

LED Downlight for 90mm hole size with 3 colour switch on the back and narrow 60° beam angle similar to Previous Halogen fittings

FEATURES:

Crystal 60° lens for attractive light distribution, suitable for high ceilings, mood lighting or for reducing Glare. All three colours are attractive and usable
 Warm (3000k), Natural (4000k) or Bright (5000k)
 No Green or Blue colour casts
 Dimmable 5-100% (depending on dimmer used)
 Built in Driver with cord and plug
 Diffuser with even spread of light and no LEDs visible.
 IC-4 Abutted and Covered certification to allow for covering with thermal insulation.
 Very high Lumens 940lm
 High CRI (colour quality)
 Frequency Free
 No UV and blue filtered
 Very long lifespan 40 000 hrs
 IP54 base - can be used under patios and eaves

SUITABLE FOR:

Patios and Eaves
 Homes
 Hotels
 Restaurants
 Shops
 Stairways
 Lobbies
 Reception areas

