

8W LED LOW GLARE ARCHITECTURAL TRI-COLOUR DOWNLIGHT GH-DL8 CCT-P





-	\sim \sim	ΝP.	 \sim	

NEW Premium architectural downlight with very attractive diffuser and 60° beam angle for an even spread of light and less glare. Essential for comfort and with no flicker in rooms with ceiling fans.

Very efficient 8w with high lumen output and high CRI, good heat dissipation and no UV. This light has three popular and practical colour output options which are adjustable by switch on the back of the light to Warm (3000k), Natural (4000k) or Bright (5000k). Lighting direction can be adjusted 0-30° for specific applications and to highlight special features. Fully dimmable.

Recommended for general lighting applications in homes, offices, supermarkets, shops, schools, hotels as well as for public areas such as stairways, lobbies, reception areas, corridors etc.

FEATURES:

- More efficient with high lumens and high CRI
- Low glare architectural design
- Adjustable to 30°
- All three colours are attractive and usable in a variety of environments
- Warm (3000k), Natural (4000k) or Bright (5000k)
- Uniform light output
- 3 Year Warranty
- Long lifespan 50 000 hours

LIEV INCORNATION				
KEY INFORMATION				
LUMEN OUTPUT	760-950 Lumens			
INPUT POWER	8W			
REPLACES	100-120W			
HOLE CUTOUT SIZE	90-95mm			
INSTALL	Recessed			
DIMMING OPTIONS	Dimmable			
TRIM COLOUR	White			
WARRANTY	3 Years			
IP RATING	IP20			
FLICKER FREE	Yes			
PHOTOMETRIC				
EFFICACY	Up to 118 Lms/W			
LUMEN OUTPUT COLOUR	Warm 3000k/Natural 4000k/Bright 5000k			
CRI	≥80			
BEAM ANGLE	60°			
ELECTRICAL				
DRIVER	Internal			
SUPPLY INPUT	AC220-240V, 50-60Hz			
POWER FACTOR	0.9			
LIFESPAN	50000Hrs			
CONSTRUCTION				
MATERIAL CONSTRUCTION	PC Lens, Plastic Coated Aluminium, White RAL 9016			
SHADE/HOUSING	Matte White with frosted PC Lens			
LOW HEAT OUTPUT	Yes			
MERCURY	No Mercury			
TOTAL WEIGHT	0.21kg per piece			
DIMENSIONS	ø106x84mm			
CERTIFICATION	SAA, IC-4, RCM			