



7/10W 360° GIMBAL DIMMABLE LED DOWNLIGHT IP65

KEY INFORMATION

LUMEN OUTPUT	700/1000 Lumens
INPUT POWER	7/10W
REPLACES	Up to 100Watt
HOLE CUTOUT SIZE	70/90mm
INSTALL	Flat surface, spring clips
DIMMING OPTIONS	Dimmable 0-100%
TRIM COLOUR	Matte white
WARRANTY	5 Years
IP RATING	IP65 waterproof, dust proof. Driver IP20
FLICKER FREE	Yes

PHOTOMETRIC

EFFICACY	100 Lumens/Watt
LIGHT OUTPUT COLOUR	Warm 3000k/Natural 4000k/Bright 6000k
CRI	>80
BEAM ANGLE	60°

ELECTRICAL

DRIVER	External
SUPPLY INPUT	AC220-240V, 50-60Hz
POWER FACTOR	>0.92
LIFESPAN	50000hrs

CONSTRUCTION

MATERIAL CONSTRUCTION	Aluminium and PMMA
SHADE/HOUSING	Matte white Recessed
LOW HEAT OUTPUT	Low heat output
MERCURY	No Mercury
TOTAL WEIGHT	350/450g/pce
DIMENSIONS	Ø75mmx27mm/Ø95x32mm/Ø110x42mm
PACKED DIMENSIONS	125x95x60mm 5/7W, 135x115x70mm 10W
CERTIFICATION	CE, IC-4, RCM, IP65

DESCRIPTION:

Fully sealed, compact gimbal downlight with high CRI, high lumen output, long lifespan and long warranty. Good heat dissipation with no flickering and no UV. Fast, push-fit termination with separate driver, dimmable, beam angle of 60° for even spread of light and less glare. Rotatable 0-360°.

FEATURES:

- 60° Beam angle for spot lighting & less glare
- Dimmable from 0-100%.
- Three colour options - Warm (3000k), natural (4000k) or bright (6000k).
- SMART option 3000-6000k (available on request)
- 0-360° Rotatable
- Maximum depth of 45mm for shallow and void ceiling
- High CRI and High Lumen output
- No flickering & no UV
- IP65 - waterproof and dust proof
- Short circuit and overload protection

SUITABLE FOR:

- Homes
- Offices
- Retail
- Supermarkets
- Shops
- Schools
- Hotels
- Public areas - stairways, reception areas,

