

99.4mm



310mm

KEY INFORMATION

| LUMEN OUTPUT | 32 000 Lumens |
|------------------|---------------------------------|
| INPUT POWER | 200W |
| REPLACES | Brighter than 400W Metal Halide |
| HOLE CUTOUT SIZE | N/A |
| INSTALL | Hanging bracket with ring |
| DIMMING OPTIONS | Dimmable with Sensor option |
| TRIM COLOUR | Black |
| WARRANTY | 4 Years |
| IP RATING | IP65 - waterproof/dustproof |
| FLICKER FREE | Yes |

| PHOTOMETRIC | |
|------------------------|-------------|
| EFFICACY | 160Lm/W |
| LIGHT OUTPUT COLOUR | 5000k (90°) |
| CRI | >70 |
| BEAM ANGLE | 90° |

ELECTRICAL

| DRIVER | Internal flicker free |
|--------------|-----------------------|
| SUPPLY INPUT | 220~240VAC, 50-60Hz |
| POWER FACTOR | >0.95 |
| LIFESPAN | 50 000hrs |

CONSTRUCTION

| MATERIAL CONSTRUCTION | Diecast aluminium housing, optical PC Lens |
|-----------------------|--------------------------------------------|
| SHADE/HOUSING | Black Aluminium |
| LOW HEAT OUTPUT | Low heat output |
| MERCURY | No Mercury |
| TOTAL WEIGHT | 3.7kg Packed |
| DIMENSIONS | Ø310x99.4mm |
| PACKED DIMENSIONS | 340x340x13mm |
| CERTIFICATION | CE, RCM |

200W SMART LED HIGH BAY 90° BEAM ANGLE

DESCRIPTION:

High Quality High Bay in 200w using branded driver and Philips LED chips. Very high brightness with 160 lumens/watt. High efficiency with PF: >0.95 and long lifespan of 5000hrs. Precise lens technology provides light exactly where it is needed, reducing light wastage. Excellent thermal design ensuring safe working temperature and long life.

Now **Smart Ready** - available with Bluetooth or Zigbee Sensor option.

FEATURES:

High reliability, high stability, high colour rendering Available in 190° beam, 5000k, suitable for ceiling heights of 5-8m. Operating temperature -30~+45°C 25% -50% Brighter than 400W Metal Halide Waterproof (IP65) PF >0.95 Extremely long lifespan 50000hrs 4 Year Warranty

SUITABLE FOR:

Sheds Factories Warehouses Garages Supermarkets Gyms Schools Halls and high ceilings (5m or less) General open areas