



P18CCT 220R 18W LED LIGHT PANEL ROUND CCT

KEY INFORMATION

LUMEN OUTPUT	1240-1380 Lumens
INPUT POWER	18W
REPLACES	120W Traditional downlight
HOLE CUTOUT SIZE	ø205mm
INSTALL	Recessed with spring clips
DIMMING OPTIONS	Non-dimmable, dimmable option available
TRIM COLOUR	White
WARRANTY	3 Years
IP RATING	IP20
FLICKER FREE	Yes

PHOTOMETRIC

EFFICACY	Up to 84Lm/W
LIGHT OUTPUT COLOUR	3000/4000/5700K - Tricolour switch
CRI	>80
BEAM ANGLE	120°

ELECTRICAL

DRIVER	Internal
SUPPLY INPUT	220-240VAC, 50-60Hz
POWER FACTOR	>0.9
LIFESPAN	40000hrs

CONSTRUCTION

MATERIAL CONSTRUCTION	White Aluminium, 9016 frame, PS Diffuser
SHADE/HOUSING	White Aluminium
LOW HEAT OUTPUT	Low heat output
MERCURY	No Mercury
TOTAL WEIGHT	0.7kg net weight
DIMENSIONS	ø205mmx21mm
PACKED DIMENSIONS	290x235x35mm
CERTIFICATION	SAA, RCM

DESCRIPTION:

Elegant ultra slim, low profile design with high brightness. Excellent energy saving with long life of 40 000hrs and low power consumption. One light is perfect for small to medium rooms, giving a clean ceiling effect with one light in the centre of the room. Very attractive and effective lighting option providing maintenance free, good quality, low cost lighting.

FEATURES:

Size: Round 220mm
Hole size: ø205mmx21mm
PF=>0.9
Tri-colour switch
Non dimmable
Instant start - suitable for sensors
Separate driver
Long lifespan - 40000hrs
3 Year Warranty
IP20 Indoors

SUITABLE FOR:

Homes
Offices
Hotels
Restaurants
Retail shops