



## P18CCT 225SQ 18W LED SQUARE MINI PANEL CCT

### KEY INFORMATION

LUMEN OUTPUT	1280-1500 Lumens
INPUT POWER	18W
REPLACES	120W Traditional downlight
HOLE CUTOUT SIZE	205x205mm
INSTALL	Recessed with spring clips
DIMMING OPTIONS	Non-dimmable, dimmable option available
TRIM COLOUR	White
WARRANTY	3 Years
IP RATING	IP20
FLICKER FREE	Yes

### PHOTOMETRIC

EFFICACY	Up to 84 Lm/W
LIGHT OUTPUT COLOUR	3000/4000/5000K - Tricolour switch
CRI	>80
BEAM ANGLE	120°

### ELECTRICAL

DRIVER	Separate
SUPPLY INPUT	220-240VAC, 50-60Hz
POWER FACTOR	>0.9
LIFESPAN	40000hrs

### CONSTRUCTION

MATERIAL CONSTRUCTION	White Aluminium, 9016 frame, PS Diffuser
SHADE/HOUSING	White
LOW HEAT OUTPUT	Low heat output
MERCURY	No Mercury
TOTAL WEIGHT	0.75kg net weight
DIMENSIONS	225x225x21mm
PACKED DIMENSIONS	290x235x35mm
CERTIFICATION	SAA, RCM

#### DESCRIPTION:

Elegant ultra slim, low profile design with high brightness. Excellent energy saving with long life of 40 000hrs and low power consumption. One light is perfect for small to medium rooms, giving a clean ceiling effect with one light in the centre of the room. Very attractive and effective lighting option providing maintenance free, good quality, low cost lighting.

#### FEATURES:

Size: Square 225mm  
Hole size: 205x205mm  
PF=>0.9  
Tri-colour switch  
Non dimmable  
Instant start - suitable for sensors  
Separate driver  
Long lifespan - 40000hrs  
3 Year Warranty  
IP20 Indoors

#### SUITABLE FOR:

Homes  
Offices  
Hotels  
Restaurants  
Retail shops