



P18S 18W LED PANEL LIGHT

KEY INFORMATION

LUMEN OUTPUT	3000k - 1530Lumens, 4000k - 1620Lumens, 5000k - 1584Lumens
INPUT POWER	18W
REPLACES	120W Traditional downlight / Up to a 3-bulb oyster fitting / 44 CFL
HOLE CUTOUT SIZE	From 55-175mm
INSTALL	Adjustable spring clips for recessed / Surface mounted with screws
DIMMING OPTIONS	Non-dimmable
TRIM COLOUR	White, Brushed chrome or Polished black chrome covers available
WARRANTY	3 Years
IP RATING	IP20
FLICKER FREE	Yes

PHOTOMETRIC

EFFICACY	90 Lm/W
LIGHT OUTPUT COLOUR	3000k/4000k/5000k - CCT switch adjustable
CRI	>80
BEAM ANGLE	110°

ELECTRICAL

DRIVER	Internal
SUPPLY INPUT	200-240VAC, 50-60Hz
POWER FACTOR	>0.9
LIFESPAN	30000hrs

CONSTRUCTION

MATERIAL CONSTRUCTION	Thermal plastic frame, PMMA, LGP, Aluminium heatsink
SHADE/HOUSING	White. Brushed chrome or polished black chrome magnetic covers optional.
LOW HEAT OUTPUT	Low heat output
MERCURY	No Mercury
TOTAL WEIGHT	0.5kg Packed
DIMENSIONS	Ø217x15mm
PACKED DIMENSIONS	235x225x43mm
CERTIFICATION	CE RCM SAA Plug

DESCRIPTION:

18W CEILING LIGHT - Oyster Light Replacement. Unique, very versatile ceiling light with three popular and practical colour output options which are selected by switch on the back of the light; Warm (3000k), Natural (4000k) or Bright (5000k). Smooth dimming effect and no flickering. High CRI, high lumen output with good heat dissipation and no UV.

FEATURES:

Ultra slim, low profile
Surface mounted or recessed.
Adjustable fitting. Hole size from 55-175mm.
Built in driver, cord and plug.
Flicker-free.
Comes standard with white cover. Optional covers in polished chrome or black polished chrome.

SUITABLE FOR:

Domestic or commercial applications
Can replace various downlights and Oyster fittings