



P18 SENSOR 18W LED PANEL LIGHT

KEY INFORMATION

LUMEN OUTPUT	3000k - 1530Lumens, 4000k - 1620Lumens, 5000k -
INPUT POWER	18W
REPLACES	120W Traditional downlight / Up to a 2-bulb oyster
HOLE CUTOUT SIZE	From 55-175mm
INSTALL	Adjustable spring clips for recessed / Surface mounted
DIMMING OPTIONS	Non-dimmable
TRIM COLOUR	White
WARRANTY	2 Years
IP RATING	IP44
FLICKER FREE	Yes

PHOTOMETRIC

EFFICACY	Up to 90 Lm/W
LIGHT OUTPUT COLOUR	3000k/4000k/5000k - CCT switch adjustable
CRI	>80
BEAM ANGLE	120°

ELECTRICAL

DRIVER	Internal
SUPPLY INPUT	240-265VAC, 50-60Hz
POWER FACTOR	>0.9
LIFESPAN	25000hrs

CONSTRUCTION

MATERIAL CONSTRUCTION	Thermal plastic frame, PMMA, LGP, Aluminium
SHADE/HOUSING	White. Brushed chrome or polished black
LOW HEAT OUTPUT	Low heat output
MERCURY	No Mercury
TOTAL WEIGHT	0.5kg
DIMENSIONS	Ø225x20mm
PACKED DIMENSIONS	240x230x47mm
CERTIFICATION	CE, RCM

DESCRIPTION:

18W CEILING LIGHT - Oyster Light Replacement. Unique, very versatile ceiling light with three popular and practical colour output options which are selected by switch on the back of the light; Warm (3000k), Natural (4000k) or Bright (5000k). High CRI, high lumen output with good heat dissipation and no UV.

Built in:

- LUX Daylight Sensor
- Motion Sensor
- Standby time options, up to 5 minutes

FEATURES:

Ultra slim, low profile
Surface mounted or recessed.
Adjustable fitting. Hole size from 55-175mm.
Built in driver, cord and plug.
Flicker-free.

SUITABLE FOR:

Domestic or commercial applications
Can replace various downlights and Oyster fittings