



P24S 24W LED PANEL LIGHT

KEY INFORMATION

LUMEN OUTPUT	3000k - 2160Lumens, 4000k - 2280Lumens, 5000k -
INPUT POWER	24W
REPLACES	180-200W Traditional downlight / Up to a 3-bulb oyster
HOLE CUTOUT SIZE	From 60-250mm
INSTALL	Adjustable spring clips for recessed / Surface mounted
DIMMING OPTIONS	Non-dimmable
TRIM COLOUR	White, Brushed chrome or Polished black chrome covers
WARRANTY	3 Years
IP RATING	IP20
FLICKER FREE	Yes

PHOTOMETRIC

EFFICACY	95 Lm/W
LIGHT OUTPUT COLOUR	3000k/4000k/5000k - CCT switch adjustable
CRI	>80
BEAM ANGLE	110°

ELECTRICAL

DRIVER	Internal
SUPPLY INPUT	200-240VAC, 50-60Hz
POWER FACTOR	>0.9
LIFESPAN	30000hrs

CONSTRUCTION

MATERIAL CONSTRUCTION	Thermal plastic frame, PMMA, LGP, Aluminium heatsink
SHADE/HOUSING	White. Brushed chrome or polished black chrome magnetic covers avail.
LOW HEAT OUTPUT	Low heat output
MERCURY	No Mercury
TOTAL WEIGHT	0.7kg
DIMENSIONS	Ø290x15mm
PACKED DIMENSIONS	310x300x43mm
CERTIFICATION	CE RCM SAA Plug

DESCRIPTION:

24W CEILING LIGHT - Oyster Light Replacement. Unique, very versatile ceiling light with three popular and practical colour output options which are selected by switch on the back of the light; Warm (3000k), Natural (4000k) or Bright (5000k). Smooth dimming effect and no flickering. High CRI, high lumen output with good heat dissipation and no UV.

FEATURES:

Ultra slim, low profile
Surface mounted or recessed.
Adjustable fitting. Hole size from 60-250mm.
Built in driver, cord and plug.
Flicker free.
Comes standard with white cover.
Optional covers in brushed chrome or black polished chrome.

SUITABLE FOR:

Domestic or commercial applications