



P25S 25W LED PANEL LIGHT

KEY INFORMATION

| | |
|------------------|--|
| LUMEN OUTPUT | 2250 Lumens |
| INPUT POWER | 25W |
| REPLACES | 180-200W Traditional downlight / 60CFL |
| HOLE CUTOUT SIZE | N/A |
| INSTALL | Surface mounted with screws |
| DIMMING OPTIONS | Dimmable |
| TRIM COLOUR | White |
| WARRANTY | 3 Years |
| IP RATING | IP54 |
| FLICKER FREE | Yes |

PHOTOMETRIC

| | |
|---------------------|---|
| EFFICACY | 90 Lms/W |
| LIGHT OUTPUT COLOUR | 3000k/4000k/6000k - CCT switch adjustable |
| CRI | >82 |
| BEAM ANGLE | 120° |

ELECTRICAL

| | |
|--------------|---------------------|
| DRIVER | Internal |
| SUPPLY INPUT | 200-240VAC, 50-60Hz |
| POWER FACTOR | >0.9 |
| LIFESPAN | 40000hrs |

CONSTRUCTION

| | |
|-----------------------|-----------------|
| MATERIAL CONSTRUCTION | Fire rated PVC |
| SHADE/HOUSING | White PVC |
| LOW HEAT OUTPUT | Low heat output |
| MERCURY | No Mercury |
| TOTAL WEIGHT | 0.95kg |
| DIMENSIONS | Ø300x40mm |
| PACKED DIMENSIONS | 310x310x500mm |
| CERTIFICATION | RCM SAA |

DESCRIPTION:

25W CEILING LIGHT - Oyster Light Replacement. Unique, very versatile, large diameter ceiling lights, colour temperature adjustable by switch - Warm (3000k) or Natural (4000k) or Bright (6000k). High CRI, high lumen output, good heat dissipation and no UV. Can be surface mounted, hole size ø300mm (25W). Multi-purpose, can be used for domestic and commercial applications.

DESCRIPTION:

Elegant, slim design
2250 Lumens, 90 Lms/W
High CRI
Flicker-free
Fire rated PVC
Built in driver and cord

SUITABLE FOR:

Domestic or commercial applications