



P36 30X120 36W LED PANEL (BACK-LIT)

KEY INFORMATION

LUMEN OUTPUT	3600 Lumens
INPUT POWER	36W
REPLACES	72W Fluorescent
HOLE CUTOUT SIZE	N/A
INSTALL	Fits suspended ceilings
DIMMING OPTIONS	Non-dimmable (dimmable drivers optional)
TRIM COLOUR	White
WARRANTY	5 Years
IP RATING	IP20
FLICKER FREE	Yes

PHOTOMETRIC

EFFICACY	100Lm/W
LIGHT OUTPUT COLOUR	5000k - Bright white
CRI	>80
BEAM ANGLE	120°

ELECTRICAL

DRIVER	External
SUPPLY INPUT	200-240VAC, 50-60Hz
POWER FACTOR	>0.9
LIFESPAN	50 000hrs

CONSTRUCTION

MATERIAL CONSTRUCTION	Aluminium frame, PMMA and PC diffuser
SHADE/HOUSING	Slim, flat white frame with frosted lens
LOW HEAT OUTPUT	Low heat output
MERCURY	No Mercury
TOTAL WEIGHT	2.5kg
DIMENSIONS	1195x295x32mm
PACKED DIMENSIONS	1260x290x375mm (approx.)
CERTIFICATION	RCM, SAA, IC-4 (panel)

DESCRIPTION:

New technology back-lit panels are more efficient with lower operational costs. Perfect for commercial use. Excellent energy saving and very efficient. Low UGR, flicker-free driver, no RF interference, no UV radiation.

FEATURES:

50 000 hrs lifespan
Rectangle (30x120cm)
5 Year Warranty
100% flicker free drivers
PF=>0.9
5000k
Fits easily to suspended ceilings

SUITABLE FOR:

Commercial use
Schools and Educational Facilities
Offices
Hospitals
Healthcare
Retail
Showrooms