



## P36P 60X60 36W LED LOW GLARE PANEL (BACK-LIT)

### KEY INFORMATION

LUMEN OUTPUT	3600 Lumens
INPUT POWER	36W
REPLACES	2 x 1.2m Tubes
HOLE CUTOUT SIZE	N/A
INSTALL	Fits suspended ceilings
DIMMING OPTIONS	Non-dimmable
TRIM COLOUR	White
WARRANTY	4 Years
IP RATING	IP20
FLICKER FREE	Yes

### PHOTOMETRIC

EFFICACY	100Lm/W
LIGHT OUTPUT COLOUR	5000k - Bright white. Blue filtered.
CRI	>80
BEAM ANGLE	120°

### ELECTRICAL

DRIVER	Internal
SUPPLY INPUT	220-240VAC, 50-60Hz
POWER FACTOR	>0.9
LIFESPAN	50 000hrs

### CONSTRUCTION

MATERIAL CONSTRUCTION	Aluminium and PC
SHADE/HOUSING	Slim, flat white frame with frosted lens
LOW HEAT OUTPUT	Low heat output
MERCURY	No Mercury
TOTAL WEIGHT	1.6kg
DIMENSIONS	595x595x32mm
PACKED DIMENSIONS	600x600x35mm
CERTIFICATION	CE, RCM, SAA (Driver)

### DESCRIPTION:

New technology premium back-lit panels are more efficient with lower operational costs. Perfect for commercial use. Excellent energy saving and very efficient. Low UGR, flicker-free driver, no RF interference, no UV radiation.

### FEATURES:

Low UGR<19 can reduce over 50% glare into eyes, increasing comfort and productivity. High Brightness - 100 Lumen/Watt LED's, 36Watt panel provides more light than 2 x 1.2m T8 fluorescent tubes. 35 000 hrs lifespan  
Square (60x60cm) or rectangular (30x120cm)  
4 Year Warranty  
100% flicker free drivers  
PF=>0.9  
5000k Blue filtered  
Fits easily to suspended or fixed ceilings

### SUITABLE FOR:

Commercial use:  
Schools and Educational Facilities  
Offices  
Hospitals  
Healthcare  
Retail  
Showrooms