



## T42 PRO 40W LED BATTEN PRO 1.2m 60K

### KEY INFORMATION

|                  |                                      |
|------------------|--------------------------------------|
| LUMEN OUTPUT     | 4700 Lumens                          |
| INPUT POWER      | 40W                                  |
| REPLACES         | 2xT8 or T5 Tubes                     |
| HOLE CUTOUT SIZE | N/A                                  |
| INSTALL          | Ceiling mounted                      |
| DIMMING OPTIONS  | Non-dimmable or Dimmable with Sensor |
| TRIM COLOUR      | White                                |
| WARRANTY         | 5 Years                              |
| IP RATING        | IP20                                 |
| FLICKER FREE     | Yes                                  |

### PHOTOMETRIC

|                     |                    |
|---------------------|--------------------|
| EFFICACY            | 117.5 lm/W         |
| LIGHT OUTPUT COLOUR | 5700k Bright white |
| CRI                 | 80                 |
| BEAM ANGLE          | 120°               |

### ELECTRICAL

|              |                     |
|--------------|---------------------|
| DRIVER       | Internal            |
| SUPPLY INPUT | 180~264VAC, 50-60Hz |
| POWER FACTOR | 0.9                 |
| LIFESPAN     | 50 000hrs           |

### CONSTRUCTION

|                       |  |
|-----------------------|--|
| MATERIAL CONSTRUCTION | Stainless steel sheet & plate with white colour coating, aluminium reflector, PC opal diffuser |
| SHADE/HOUSING         | White with frosted PC lens   |
| LOW HEAT OUTPUT       | Low heat output  |
| MERCURY               | No Mercury   |
| TOTAL WEIGHT          | 1kg / 1.2kg packed   |
| DIMENSIONS            | 1016x64x62mm   |
| PACKED DIMENSIONS     | 1230x70x66mm/1 pce   |
| CERTIFICATION         | SAA, CE, RCM   |

### DESCRIPTION:

High quality, slim fitting LED batten light with easy installation and add on options  
-With overload protection, over-voltage protection, short circuit protection, polycarbonate impact resistant diffuser and excellent thermal management.

### FEATURES:

High performance, very bright, 4700 lumens Flicker-free  
Industrial Strength  
Very long Life 50 000hrs  
Suitable for Conduits  
Optional inbuilt motion sensor  
Optional Battery Back up  
Optional Dimmable  
5 YEAR WARRANTY

### SUITABLE FOR:

Can be used in a variety of retail, commercial and industrial settings:  
Schools  
Office buildings  
Workshops/factories  
Parking garages