22 W LED Track Light – Tricolour, White or Black

An adjustable LED spotlight that clicks into a ceiling track, for shops, galleries, offices and homes.



KEY FEATURES

- Beam adjusts from 24° (narrow) to 60° (wide) by turning the lens
- Head tilts 90° and turns 355° to aim the light
- 3 colours on a switch: 3000 K, 4000 K or 5700 K
- High colour quality, CRI 90
- Driver built into the track adapter – no separate box
- Matte white or matte black aluminium body

IN THE BOX

- 1 × 22 W track light with track adapter (driver built in)
- Track sold separately (1 m, 1.5 m or 2 m) – each length comes with a connector and end cap

Certification: RCM, Global Mark

SPECIFICATIONS

Power	22 W
Input voltage	220–240 VAC, 50/60 Hz
Light output	2018-2310 lm
Colour temperature	3000 K / 4000 K / 5700 K (switch on the light)
Colour rendering (CRI)	90
Beam angle	24–60° adjustable
Aiming	Tilts 90°, turns 355°
Dimmable	No
IP rating	IP20 – indoor, dry areas only
Track type	3-wire, single-circuit track
Size	160 × 214 × 65 mm
Weight	0.52 kg
Material	Aluminium body, polycarbonate optic
Operating temperature	−20 °C to +35 °C
Lifespan	50,000 hours
Warranty	3 years

OPTIONS

Option	Body colour
22 W White Track Light	Matte white
22 W Black Track Light	Matte black

Installation: licensed electrician required – see the installation guide. Keep your invoice for warranty.

22 W LED Track Light – Tricolour, White or Black

ABOUT THIS PRODUCT

An adjustable 22 W LED spotlight that clicks into a standard 3-wire single-circuit ceiling track, ideal for shops, galleries, showrooms, offices and feature walls at home. The beam zooms from 24° to 60° so you can highlight one display or wash a wider area, and the head tilts 90° and turns 355°. High colour rendering (CRI 90) makes products and artwork look true to life, and a switch on the light sets warm, natural or cool white.

SIZES & VERSIONS

White	Matte white body
Black	Matte black body

MORE DETAILS

Electrical class	Class II
Flicker	Flicker index 5% (no risk)
Harmonic distortion (THD)	Below 20% at 230 V
Standby power	Below 0.5 W
Colour consistency	SDCM 5 or less
Impact rating	IK03

SAFETY & COMPLIANCE

Compliance details being updated

Equipment risk level	Level 1

Greenhse supplies this product for sale in Australia. Its updated compliance documents are being finalised. Please contact Greenhse for the latest certificate details before installation.