90 mm 8 W LED Downlight – Tricolour, Flat Cover

A slim, dimmable 8 W downlight for a 90 mm hole, with three colours to choose from, for homes, offices and shops.



KEY FEATURES

- Choose warm 3000 K, natural 4000 K or bright 5700 K with a switch
- Dimmable with most LED-rated wall dimmers
- IC-4 rated – ceiling insulation can touch and cover it
- Built-in driver with lead and plug
- White cover standard; black or brushed chrome cover optional
- IP54 at the front – resists dust and splashes

IN THE BOX

- 1 × 8 W downlight with built-in driver
- Lead with plug, attached to the light
- Cover in the colour you ordered (white is standard)

SPECIFICATIONS

Power	8 W
Input voltage	220–240 V AC, 50 Hz
Light output	660–800 lm
Colour temperature	3000 K / 4000 K / 5700 K (switch on the back)
Colour rendering (CRI)	80 or more
Beam angle	100°
Dimmable	Yes – triac (phase-cut) dimmers
IP rating	IP54 front cover / IP40 inside the ceiling
Insulation contact	IC-4 – can be covered with insulation
Cut-out	90–95 mm
Size	Ø106 × 45 mm
Material	Plastic body, frosted PC diffuser, white RAL 9016
Driver	Built in, with lead and plug
Power factor	0.9 or more
Lifespan	50,000 hours
Warranty	3 years

OPTIONS

Cover	Note
White	Standard
Brushed chrome	Optional extra
Matte black	Optional extra

Installation: licensed electrician required – see the installation guide. Keep your invoice for warranty.

90 mm 8 W LED Downlight – Tricolour, Flat Cover

ABOUT THIS PRODUCT

A slim, dimmable 8 W downlight for standard 90 mm holes, with a flat cover that sits neatly against the ceiling. It suits living rooms, bedrooms, hallways, offices and shops, and makes an easy swap for old halogen downlights. A switch on the back lets you choose warm, natural or cool white, and it dims on a compatible LED dimmer. The built-in driver comes with a lead and plug, and white, brushed chrome or matte black covers let you match your room.

MORE DETAILS

Driver efficiency	80% or higher
Standby power	Under 0.5 W
Operating temperature	−20 to 40 °C
LED type	2835 SMD
Colour consistency	SDCM under 6
Surge protection	500 V (line to neutral)

SAFETY & COMPLIANCE

Compliance details being updated

Equipment risk level	Level 2

Greenhse supplies this product for sale in Australia. Its updated compliance documents are being finalised. Please contact Greenhse for the latest certificate details before installation.