Airforce 3-in-1 DC Bathroom Heater

A ceiling bathroom heater with two heat lamps, an exhaust fan and an LED light, for small to medium bathrooms.



KEY FEATURES

- 2 × 275 W infrared heat lamps for instant warmth
- 22 W brushless DC exhaust moves up to 400 m³/hr
- 12 W LED light, 1100 lm, 4200 K natural white
- Fan turns on by itself if the unit gets too hot
- 3-gang wall switch, 1.5 m duct and outside grille included

IN THE BOX

- 1 × Airforce bathroom heater with LED panel
- 2 × 275 W infrared heat lamps
- 1 × Ø 100 mm flexible duct, 1.5 m
- 1 × exterior vent grille
- 1 × 3-gang wall switch plate

SPECIFICATIONS

Input voltage	220–240 V AC, 50 Hz
Total power	584 W max
Heat	2 × 275 W infrared heat lamps (E27)
Exhaust motor	22 W brushless DC
Air extraction	Up to 400 m³/hr
Light	12 W LED, 1100 lm, 4200 K, not dimmable
Noise	Under 45 dB
Cut-out	375 × 205 mm
Size	400 × 230 mm
Duct outlet	Ø 100 mm side outlet with draft stopper
IP rating	IPX2
Electrical class	Class II
Clearance above unit	100 mm min.
Control	3-gang wall switch (included)
Finish	Matte white
Warranty	3 years replacement

Installation: licensed electrician required – see the installation guide. Keep your invoice for warranty.

Airforce 3-in-1 DC Bathroom Heater

ABOUT THIS PRODUCT

The Airforce is a 3-in-1 ceiling unit that heats, ventilates and lights a small to medium bathroom. Two 275 W infrared heat lamps give instant warmth on cold mornings, a quiet 22 W brushless DC exhaust motor clears steam and odours, and a 12 W LED panel provides bright natural white light. A built-in thermal switch starts the fan by itself if the unit gets too hot. It comes with a 3-gang wall switch, flexible duct and outside grille, so an electrician has everything needed for a neat installation in a flat ceiling.

MORE DETAILS

Weight	2.0 kg
Air extraction	111 L/s (measured with 100 mm duct)
Mounting height	At least 2.1 m above the floor
Distance from walls	At least 250 mm
Supply	Needs a permanent (unswitched) active for the overheat fan
Mounting	Swing clips with screws, flat ceilings only
Packed size	475 × 299 × 322 mm, 3.5 kg

SAFETY & COMPLIANCE

Compliance details being updated

Greenhse supplies this product for sale in Australia. Its updated compliance documents are being finalised. Please contact Greenhse for the latest certificate details before installation.