greenhse Technologies

COMPLIANCE
Details on page 2

SPEC SHEET
Product code: blizzard-exhaust-cct-small

Blizzard DC Exhaust Fan & Light – Small

A quiet, energy-saving ceiling exhaust fan with a built-in tricolour LED light, for small to medium bathrooms, laundries and kitchens.



KEY FEATURES

- Energy-saving 20 W brushless DC motor
- Moves up to 450 m³/hr of steamy air
- Built-in 15 W LED light, 1100 lm, 3 colour choices
- 100 mm and 150 mm duct adaptors with back-draft shutter included
- Fascia pulls off for easy cleaning
- Fits from below the ceiling with swing clips

IN THE BOX

- 1 × Blizzard exhaust fan (ø270 mm fascia, built-in LED light)
- 1 × 100 mm duct adaptor with back-draft shutter
- 1 × 150 mm duct adaptor with back-draft shutter
- 1 × cutting template
- 1 × instruction sheet

SPECIFICATIONS

Motor	20 W brushless DC
Input voltage	220–240 V AC, 50 Hz
Air extraction	Up to 450 m³/hr
Light	15 W LED, 1100 lm
Colour temperature	3000 K / 4200 K / 6000 K (switch on the fascia)
Noise	36 dB at 1.5 m
Fascia size	ø270 mm
Cut-out	ø255 mm
Height above ceiling	185 mm (fascia adds 30 mm below)
Duct outlet	100 mm or 150 mm adaptor with back-draft shutter
IP rating	IPX4
Electrical class	Class I (earthed)
Connection	Two plug leads – fan and light
Mounting	Swing clips with screws, flat ceiling only
Finish	White
Warranty	5 years replacement

Installation: licensed electrician recommended – see the installation guide. Keep your invoice for warranty.

Blizzard DC Exhaust Fan & Light – Small

ABOUT THIS PRODUCT

The Blizzard Small is a compact, energy-saving ceiling exhaust fan with a built-in 15 W tricolour LED light, made for small to medium bathrooms, laundries and kitchens. The 20 W brushless DC motor quietly moves up to 450 m³ of air an hour, so steam clears fast without a noisy, power-hungry motor. Choose warm white, cool white or daylight with the fascia switch. 100 mm and 150 mm duct adaptors with back-draft shutters are included, and it carries a 5-year replacement warranty.

MORE DETAILS

Material	Plastic
Motor speed	About 1350 rpm
Mounting height	At least 2.1 m from the floor to the bottom of the fan
Space above	Leave 50 to 100 mm between the fan and the roof
Long duct runs	Still about 50% of peak airflow with 10 m of 150 mm duct
Packed size	330 × 238 × 280 mm, 2.2 kg

SAFETY & COMPLIANCE

Compliance details being updated
Ask Greenhse for the current compliance documents: (08) 9297 2969

Greenhse supplies this product for sale in Australia. Its updated compliance documents are being finalised. Please contact Greenhse for the latest certificate details before installation.