Blizzard DC Exhaust Fan – Large

A quiet, energy-saving ceiling exhaust fan for larger bathrooms, laundries and kitchens.



KEY FEATURES

- Energy-saving 40 W DC motor
- Moves up to 600 m³/hr of steamy air
- 100 mm and 150 mm duct adaptors with backdraft shutter included
- Fascia pulls off for easy cleaning
- Fits from below with swing clips

IN THE BOX

- 1 × Blizzard exhaust fan (Ø330 mm fascia)
- 1 × 100 mm duct adaptor with back-draft shutter
- 1 × 150 mm duct adaptor with back-draft shutter
- 1 × cutting template
- 1 × instruction sheet

SPECIFICATIONS

Motor	40 W brushless DC
Input voltage	220–240 V AC, 50 Hz
Air extraction	Up to 600 m³/hr
Noise	41 dB at 1.5 m
Fascia size	Ø330 mm
Cut-out	Ø300 mm
Height above ceiling	185 mm; fascia adds 30 mm
Duct outlet	100 mm or 150 mm adaptor with back-draft shutter
IP rating	IPX4
Electrical class	Class I (earthed)
Connection	Plug and lead
Mounting	Swing clips with screws, flat ceiling only
Finish	White
Warranty	5 years replacement

Installation: licensed electrician recommended – see the installation guide. Keep your invoice for warranty.

Blizzard DC Exhaust Fan – Large

ABOUT THIS PRODUCT

The Blizzard Large is a high-performing ceiling exhaust fan for larger bathrooms, laundries and kitchens. Its 40 W brushless DC motor moves up to 600 m³ of steamy air an hour at just 41 dB, using far less power than a typical AC exhaust fan and running cooler for a longer life. Both 100 mm and 150 mm duct adaptors with back-draft shutters are included, so it suits most ducting without extra parts. The fascia pulls off for cleaning and it is backed by a 5-year replacement warranty.

MORE DETAILS

Material	Plastic
Motor speed	About 1050 rpm
Mounting height	At least 2.1 m from the floor to the bottom of the fan
Space above	Leave 50 to 100 mm between the fan and the roof
Long duct runs	Still about 50% of peak airflow with 10 m of 150 mm duct
Packed size	368 × 238 × 340 mm, 3.0 kg

SAFETY & COMPLIANCE

Compliance details being updated

Greenhse supplies this product for sale in Australia. Its updated compliance documents are being finalised. Please contact Greenhse for the latest certificate details before installation.