Glenelg Ambient Up/Down Wall Light – White or Charcoal

An outdoor up/down wall light with clear side lenses, for pillars, doors, steps, paths and garages.



KEY FEATURES

- Light up and down plus a soft glow through the side lenses
- Comes with 2 × 4 W LED GU10 globes, warm white 3000 K
- Die-cast aluminium with hard-wearing powder coat
- Clear tempered glass lens
- IP65 – made for outdoor walls
- White or charcoal finish

IN THE BOX

- 1 × Glenelg Ambient up/down wall light
- 2 × 4 W LED GU10 globes (fitted)

SPECIFICATIONS

Power	2 × 4 W LED GU10 globes (included)
Input voltage	240 V AC
Light output	Up to 600 lm (2 × 300 lm)
Colour temperature	3000 K (warm white)
Lamp holder	2 × GU10, max 35 W each
Dimmable	No
IP rating	IP65
Size	241 × 80 mm, 112 mm from the wall
Material	Die-cast aluminium, tempered glass lens
Finish	White or charcoal powder coat
Electrical class	Class I (must be earthed)
Warranty	3 years replacement

OPTIONS

Option	Finish
Glenelg Ambient Up/Down – White	White
Glenelg Ambient Up/Down – Charcoal	Charcoal

Installation: licensed electrician required – see the installation guide. Keep your invoice for warranty.

Glenelg Ambient Up-Down Wall Light – White or Charcoal

ABOUT THIS PRODUCT

A classic exterior up and down wall light with a side lens that adds a soft ambient glow around the fitting. It uses two replaceable GU10 LED globes, supplied, giving warm 3000 K light. The die-cast aluminium body and tempered glass are sealed to IP65, so it is made for outdoor walls at front doors, garages, patios and pathways. It comes in white or charcoal powder coat to suit your home, and is backed by a 3 year replacement warranty.

MORE DETAILS

Globes	2 × GU10 LED, warm white 3000 K, replaceable
Light direction	Up, down and soft side glow
Mounting	Surface wall mount

SAFETY & COMPLIANCE

Compliance details being updated

Equipment risk level	Level 1

Greenhse supplies this product for sale in Australia. Its updated compliance documents are being finalised. Please contact Greenhse for the latest certificate details before installation.