BATTERY POWERED
No mains connection · see p.2

SPEC SHEET
Product code: remote-control-grp

LED Wireless Remote Controls – 2.4 GHz

Hand-held, round and glass wall-panel 2.4 GHz remotes to dim and change the colour of LED strip, garden and star lights through a Greenhse controller.



KEY FEATURES

- 2.4 GHz wireless, up to 30 m range
- Brightness 1–100% on every model
- Single zone or 4-zone models – control up to 4 groups
- Single colour, colour temperature (CCT) and RGB+CCT models
- Hand-held, round sunrise or glass wall-panel styles
- White or matte black finishes

IN THE BOX

- 1 × remote control (model you ordered)

SPECIFICATIONS

Frequency	2.4 GHz RF
Control distance	Up to 30 m
Power	3 V – 2 × AAA batteries
Dimming	1–100%
Zones	Single zone or 4 zones (model dependent)
Works with	Greenhse 2-in-1 and 3-in-1 strip controllers (standard and smart)
Glass panel size	86 × 86 mm
Finish	White or matte black
Operating temperature	-10 °C to 40 °C
Warranty	2 years

OPTIONS

Remote	Finish	Zones	Controls
Hand remote	White	4	Dimming + colour temperature
Premium hand remote	Matte black	1	Dimming + colour temperature
Premium hand remote	Matte black	4	RGB + colour temperature + dimming
Hand remote	White	1	RGB + colour temperature + dimming
Hand remote	White	4	RGB + colour temperature + dimming
Sunrise round remote	Black or white	1	Dimming + colour temperature
Glass panel remote	White or black	4	Dimming
Glass panel remote	White (CCT) / black or white (RGB+CCT)	4	CCT or RGB+CCT + dimming

Installation: licensed electrician recommended – see the installation guide. Keep your invoice for warranty.

LED Wireless Remote Controls – 2.4 GHz

ABOUT THIS PRODUCT

Greenhse 2.4 GHz wireless remotes control your LED strips, garden lights and star lights through a Greenhse 2-in-1 or 3-in-1 controller. Choose a hand-held remote, a premium matte black remote, a round sunrise remote or a glass wall panel, with single zone or 4 zone models so you can run several areas separately. Depending on the model you can dim, change colour temperature or choose full colour. They run on two AAA batteries and work up to 30 m away.

MORE DETAILS

Electrical class	Battery powered, 3 V, no mains connection
Pairing	Linked to the controller after pressing its SET button
Zones	Each zone controls its own group of controllers

SAFETY & COMPLIANCE

Battery powered remote control
No mains connection. Not prescribed electrical equipment under the EESS.

Equipment risk level	Not prescribed (extra-low voltage)

Battery powered products are not prescribed electrical equipment under the EESS. Use the battery type shown on page 1.