Quick Connect Plug Base – Single 10 A

A fast-wiring single 3-pin surface socket for plug-in downlights, panels, fans and high bays.



KEY FEATURES

- Single 3-pin 10 A socket for plug-in light fittings
- Quick wiring: pins pierce the wire insulation as the lid closes
- Only the outer sheath is stripped – no stripping of single wires
- Takes 1–2.5 mm² stranded or solid cable
- Strip-length guide on the lid, colour-coded wire channels

IN THE BOX

- Box of 10 quick connect plug bases

SPECIFICATIONS

Type	Single surface socket, insulation-piercing quick connect
Rating	10 A, 250 V AC
Socket	Australian 3-pin
Mounting	Surface mount
Cable size	1–2.5 mm², stranded or solid
Sheath strip length	45 mm
Connection	Insulation-piercing pins, locking lid
Colour	White
Pack	Box of 10
Warranty	5 years

Installation: licensed electrician required – see the installation guide. Keep your invoice for warranty.

Quick Connect Plug Base – Single 10 A

ABOUT THIS PRODUCT

The Quick Connect plug base is a single 10 A, 3-pin surface socket that makes wiring plug-in downlights, panels, fans and high bays much faster. There is no need to strip each wire: you strip only the outer sheath, lay the cores in the colour-coded channels and close the lid, and the pins pierce the insulation to make the connection. It takes 1 to 2.5 mm² solid or stranded cable and is sold in boxes of 10, ideal for electricians fitting out new builds and renovations.

MORE DETAILS

Lid	Lever locks shut, needs a small screwdriver to reopen
Re-use	Possible, but use fresh pin positions on the cable
Strip guide	Printed on the lid

SAFETY & COMPLIANCE

Compliance details being updated

Equipment risk level	Level 3

Greenhse supplies this product for sale in Australia. Its updated compliance documents are being finalised. Please contact Greenhse for the latest certificate details before installation.