Star Light Driver – 3, 4 or 6-Pin

The 240 V driver that powers Greenhse 3 W star lights – choose 3, 4 or 6 ports.



KEY FEATURES

- Powers Greenhse 3 W, 30 mm star lights
- 3-pin runs 1–3 lights – not dimmable
- 4-pin runs 3–4 lights – dimmable
- 6-pin runs 3–6 lights – dimmable
- Works with leading or trailing edge dimmers
- Lights plug straight into the connector box

IN THE BOX

- 1 × star light driver (3, 4 or 6-pin) with connector box

SPECIFICATIONS

Type	LED driver for 3 W star lights – "pin" = number of light ports
Input voltage	3-pin: 220–260 V AC; 4/6-pin: 200–240 V AC (50/60 Hz)
Output	3-pin: 2.5–10 V DC, 620 mA; 4/6-pin: 9–24 V DC, 700 mA
Lights per driver	3-pin: 1 to 3 · 4-pin: 3 to 4 · 6-pin: 3 to 6
Dimmable	3-pin: no; 4-pin and 6-pin: yes
Dimmer type	Leading or trailing edge (4/6-pin)
Dimming range	3–100% (4/6-pin)
Light connection	Plug-in connector box – lights plug straight in
Protection	Short-circuit and overload protected (4/6-pin)
Max. ambient temperature	45 °C (4/6-pin)
Approvals	RCM (4 and 6 pin drivers)

OPTIONS

Code	Driver	Runs	Dimmable
DL03-3driver	3-pin	1–3 lights	No
DL03-4driver	4-pin	3–4 lights	Yes
DL03-6driver	6-pin	3–6 lights	Yes

Installation: licensed electrician required – see the installation guide. Keep your invoice.

Star Light Driver – 3, 4 or 6-Pin

ABOUT THIS PRODUCT

Greenhse star light drivers power our 3 W, 30 mm LED star lights from 240 V. Each driver has a plug-in connector box, so the lights simply plug straight in. The 3-pin driver runs one to three lights without dimming. The 4-pin and 6-pin drivers run three to six lights and dim from 3 to 100% on a compatible leading or trailing edge wall dimmer. The dimmable drivers are certified to Australian safety standards and are double insulated.

SIZES & VERSIONS

DL03-4driver, 4-pin	Certified GMA-521895-EA, valid to 13 Feb 2030
DL03-6driver, 6-pin	Certified GMA-521895-EA, valid to 13 Feb 2030
DL03-3driver, 3-pin	Australian certificate pending

MORE DETAILS

Colour / finish	White case; 4 and 6 pin dimmable drivers have green end covers, 3 pin driver has black end covers
Input current (4/6-pin)	0.15 A
Case temperature (4/6-pin)	tc 85 °C
No-load output (4/6-pin)	26 V DC maximum
IP rating	IP20, indoor

SAFETY & COMPLIANCE

Electrical safety certified for Australia
Certificate GMA-521895-EA, valid to 13 Feb 2030

RCM

Electrical safety certificate	GMA-521895-EA (valid to 13 Feb 2030)
Certificate covers	The 4-pin and 6-pin dimmable drivers
Compliance mark	RCM (Regulatory Compliance Mark) for electrical safety and EMC
Equipment risk level	Level 3
Greenhse EESS registration	E2026002449 (registered to 6 Feb 2027)
Tested to	AS 61347.2.13:2018; AS/NZS 61347.1:2016 Amd 1: 2018
Also	Class II (double insulated), IP20, per certificate
Also	Classified IC (per certificate)

Greenhse Technologies is the registered Australian responsible supplier for this product on the national Electrical Equipment Safety System (EESS). Certificate numbers can be checked on the public EESS database at eess.gov.au.