# Supernova II 3-in-1 Bathroom Heater – 2 Lamp

A ceiling bathroom heater with two heat lamps, an exhaust fan and a two-colour LED panel for small to medium bathrooms.



## KEY FEATURES

- 2 × 275 W infrared heat lamps for instant warmth
- 40 W ball-bearing exhaust moves up to 500 m³/hr
- 12 W LED panel, up to 900 lm, 3000 K or 5000 K
- Fan turns on by itself if the unit gets over 80 °C
- 3-gang wall switch, ducting, outside grille and clamps included

## IN THE BOX

- 1 × Supernova II heater unit
- 2 × 275 W infrared heat lamps
- 1 × 3-gang wall switch
- 1 × flexible aluminium duct
- 1 × exterior grille and duct clamps

## SPECIFICATIONS

| | |
|---|---|
| **Input voltage** | 240 V |
| **Heat** | 2 × 275 W infrared heat lamps (E27, R125) |
| **Exhaust motor** | 40 W, long-life ball bearing |
| **Air extraction** | Up to 500 m³/hr (138 L/s) |
| **Light** | 12 W LED panel, not dimmable |
| **Light output** | 800 lm (3000 K) / 900 lm (5000 K) |
| **Colour temperature** | 3000 K warm white / 5000 K daylight |
| **Noise** | 45 dB or less |
| **Cut-out** | 430 × 250 mm |
| **Size** | 480 × 300 mm, 200 mm high |
| **IP rating** | IPX2 |
| **Use** | Indoor only, ceilings up to 2.4 m |
| **Control** | 3-gang wall switch (included) |
| **Finish** | White |
| **Warranty** | 3 years replacement |

**Installation:** licensed electrician required – see the installation guide. Keep your invoice for warranty.

# Supernova II 3-in-1 Bathroom Heater – 2 Lamp

## ABOUT THIS PRODUCT

The Supernova II is a 3-in-1 ceiling bathroom heater with two 275 W infrared heat lamps, a powerful exhaust fan and a two-colour LED panel. The 40 W ball-bearing fan moves up to 500 m³ of air an hour with an anti-backdraft stopper, so steam clears quickly. The 12 W LED panel switches between 3000 K warm white and 5000 K daylight. A thermostat runs the fan automatically if the unit gets over 80 °C. It suits small to medium bathrooms with ceilings up to 2.4 m.

## MORE DETAILS

| | |
|---|---|
| **Material** | Plastic |
| **Fan size** | 150 mm |
| **Air extraction** | Up to 8.3 m³ per minute |
| **Clearance** | 150 mm above the unit, 400 mm from walls |
| **Backdraft** | Anti-backdraft stopper on the outlet |

## SAFETY & COMPLIANCE

**Compliance details being updated**

Greenhse supplies this product for sale in Australia. Its updated compliance documents are being finalised. Please contact Greenhse for the latest certificate details before installation.